



JusEV H-Series AC Charger 7.4kW....22kW - Attached Cable T2

Specifications

Rated Power	7.4kW, 11kW, 22kW
Type of Connection	1P+N+PE, 3P+N+PE, 6-10mm ²
Nominal Supply	230V AC±15%, 400V AC±15%
Rated Frequency	50Hz/60Hz
Adjustable Current	6A-32A Variable(Via APP)
Over Current Protection	40A Supply (external MCB)
RCD Protection	Built-in 30mA Type A RCD+6mA DC Protection(Equivalent to Type B)
Earthing Arrangement	Built-in O-PEN Protection
Standby Power Consumption	<8W
Integrated Protections	Over and under voltage, power overload, short circuit, dispersion currents, missing ground connection, surge, over temperature
Connectivity	Bluetooth/WiFi/Ethernet/4G/RS485 Control charging with the Smart APP Built-in RFID reader, OCPP 1.6J
Solar Compatibility	ECO, ECO+, and Fast charging modes
Load Balancing	Up to 32 units can be connected
Installation Network	TN, IT, and TT
Housing Material/Enclosure	PC+ASA(UL94 V-0 Fire Rated-the Highest Flame Classification)
Mounting	Wall mounting, pedestal mounting
Socket	IEC 62196 Type 2, IP55 hinged lid, electrical lock(Compliance requested)
Protection (Enclosure)	IP55 (Socketed), IP65 (Tethered), IK10
Operating Temperature	-25°C -50°C
Humidity	5%~98% non-condensing
Installation	Indoor / Outdoor
Dimensions (HxWxD)	260*260*100mm
Weight	Socketed 2.5kg, Tethered 5kg
Certification	CE, UKCA, RoHS, REACH(TUV), MyHIAU

